

Steinlite SL95 Moisture Meter

The Steinlite SL95 NTEP Moisture Meter, distributed by Seedburo, is one of the most reliable and user-friendly moisture meters available. It is fully automatic and requires no pre-weighing of your product. The SL95 is approved for commercial use, is NTEP certified and produces a reading of moisture percentage, test weight and sample temperature within 8 seconds. The tester has two RS232 type serial communication ports and can be connected to both the SLPrinter and your desktop computer at the same time.

The Steinlite SL95 is factory calibrated for standard grains such as Barley, Corn, Oats, Soybean, Sunflower and Wheat. Over 1000 different calibrations of your choice can be loaded on the meter (please contact us or visit our web site for a list of these commodities) at the time of order. Simply turn the tester on, select the calibration or grain to be tested, pour in your sample (about 450 grams) and the infrared sensors in the hopper ensures sufficient sample size is used without any pre-weighing. Press the LOAD key and the moisture will be displayed from the LCD display within 8 seconds. The moisture range will read between 1–30% depending upon the product and grain temperature range is 35–110°F. The SL95 operates from 90–264 Volts, 43–66Hz AC grounded outlet. There is no need to select a voltage in order to operate this tester. **No. SL95:** Net wt: 30 lbs, Actual dims: 14" (L) x 12" (W) x 16" (H), Ship wt: 35 lbs, Ship dims: 19" (L) x 17" (W) x 21" (H). **No. SLPrinter:** Net wt: 3 lbs, Actual dims: 10" (L) x 12" (W) x 5" (H), Ship wt: 4 lbs, Ship dims: 12" (L) x 14" (W) 8" (H). **MADE IN THE USA.**



Steinlite Moisture Meter, 110/220V, 50/60Hz.....	No. SL95
SL-Printer, 110, 220V.....	No. SLPRINTER

Steinlite SB900 Moisture Tester

The Steinlite SB900 Moisture Tester, distributed by Seedburo, provides fast and accurate results for up to 500 different grains, seeds and nuts. The tester is pre-programmed at the factory to test common grains such as Barley, Corn, Flaxseed, Milo, Oats, Rice, Rye, Soybean, Sunflower and Wheat. An additional module, plugged into the side of the tester, can be calibrated to hold an additional 250 calibrations (visit our web site for the listing). The module is supplied at no charge if extra calibrations are specified at the time your order is placed.

Testing is simple. Turn the power on, wait for the unit to automatically balance itself, and select the commodity you want to test from the display, enter the commodity ID number and test weight (optional). Next, weigh your sample (150–250 gram sample is the norm) and place your product in the funnel. Release the grain into the test cell and measurement takes approximately 15 seconds. The tester automatically corrects for temperature. A compressor block, for lightweight or fluffy products such as Cottonseed, Wheat middlings and Sugar Beet pulp is also available as well as a funnel for Nuts. A printer for individual tickets can also be purchased. The SB900 will be supplied with the standard calibrations and grain funnel unless specified otherwise. Operates on 110/240V, 50/60Hz. Net wt: 35 lbs, Actual dims: 18" (L) x 10" (W) x 12" (H), Ship wt: 40 lbs, Ship dims: 27" (L) x 15" (W) x 17" (H). **MADE IN THE USA.**



Steinlite Moisture Tester, 110/240V, 50/60Hz.....	No. SB900
Additional Grain Calibration Module.....	No. SB-MODULE
Nut Funnel (Required with Some Calibrations).....	No. SB-NFUNNEL
Compressor Block and Funnel (Required with Some Calibrations).....	No. SB-BLOCK
Optional Printer, 110/220V, 50/60Hz.....	No. SB-PRINTER